



Applications

CCP 210 pellets have been specially designed to remove or destroy airborne acidic gases by oxidation. They offer especially high reactivities and removal capabilities to achieve very long lifetimes, even under high contaminant concentration conditions. CCP 210 pellets con-

sist of a composite of sodium permanganate and potassium permanganate at a minimum of 10 % by weight. The active ingredients are evenly distributed in the porous structure to provide optimum performance, lifetime and reactivity.

SPHERES MADE OF ALUMINUM OXIDE WITH 10 % SODIUM AND POTASSIUM PERMANGANATE		CCP 210
Bulk density	kg / m ³	800 (+/- 5%)
Nominal diameter of spherical pellets	mm	3.8
Moisture content (approx.)	%	20
Crush strength (minimum)	kg	2
Removal capacity for H ₂ S of own weight*	%	25
Removal capacity for SO ₂ of own weight*	%	12
Compliance with UL classification	Class	1
Minimum design efficiency	%	99.5
Typical air velocity	m/s	0.3 - 2.5
Suitable for relative air humidities	%	10 - 95
Temperature range	°C	-20 - +51
Remaining lifetime analysis	possible	yes

DELIVERY NOTES

Weight per box	kg	22.7
Box dimensions (LxWxH)	mm	320 x 320 x 340

CONTAMINANT GASES

CCP 210 pellets are especially recommended for all contaminant gases highlighted in lightblue. Choose other ChemControl pellets for all contaminant gases marked in darkblue.

- 1 Hydrogen sulfide (H₂S)
- 2 Sulfur dioxide (SO₂)
- 3 Other oxides of sulfur
- 4 Nitrogen oxides (NO_x)
- 5 Chlorine
- 6 Ammonia
- 7 Formaldehyde
- 8 Hydrocarbons
- 9 Mercaptans
- 10 Low molecular weight organic acids
- 11 Volatile organic compounds (VOCs)

If you require information and pellet selection assistance for contaminant gases not listed here, please consult your Viledon® partner.

* tested in broad conformity with ASTM International Standard D6646-03



UL900 certified

The figures given are mean values subject to tolerances due to normal production fluctuations. Our explicit written confirmation is always required for the correctness and applicability of the information involved in any particular case. Subject to technical alterations.

AIRWATEC sa

4700 Eupen, Belgium

Phone +32 (0) 87 598330 | Fax +32 (0) 87 598440

info@airwatec.com | www.airwatec.com



airwatec
AIR AND WATER TECHNOLOGIES

AT A GLANCE - VILEDON CHEMCONTROL PELLETS

<p>CCP 104</p> <p>1 2 3 4 7 9 10</p>		<p>CCP 610</p> <p>5 8 11</p>	
<p>CCP 108</p> <p>1 2 3 4 7 9 10</p>		<p>CCP 810</p> <p>1 2 4 8 11</p>	
<p>CCP 210</p> <p>1 2 3 4 7 9 10</p>		<p>CCP 830</p> <p>1 2 3 4 8 11</p>	
<p>CCP 310</p> <p>1 2 3 5</p>		<p>CCP 840</p> <p>1 2 5 8 11</p>	
<p>CCP 510</p> <p>5</p>		<p>CCP 903</p> <p>6</p>	

Pellets are especially recommended for all contaminant gases highlighted in lightblue ●

- 1 Hydrogen sulfide (H₂S)
- 2 Sulfur dioxide (SO₂)
- 3 Other oxides of sulfur
- 4 Nitrogen oxides (NO_x)
- 5 Chlorine
- 6 Ammonia
- 7 Formaldehyde
- 8 Hydrocarbons
- 9 Mercaptans
- 10 Low molecular weight organic acids
- 11 Volatile organic compounds (VOCs)

Please note

Other ChemControl pellets are available on request - especially custom formulations with impregnations for specific contaminants gases. All application information provided are subject to on-site conditions, specific application requirements and potential alternating effects by combining several ChemControl pellets in multi-stage units. Please consult your local Viledon® partner for further information.

AIRWATEC sa

4700 Eupen, Belgium

Phone +32 (0) 87 598330 | Fax +32 (0) 87 598440

info@airwatec.com | www.airwatec.com

